

File E179745
Project 04CA02615

January 13, 2004

REPORT

on

COMPONENTS - SWITCHES, INDUSTRIAL CONTROL

DONGGUAN SANYOU ELECTRICAL
APPLIANCES CO LTD
Guangdong, China

Copyright © 2004 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above named company to reproduce the latest pages of that portion of this Report consisting of this Cover Page through Page 3.

DESCRIPTION

PRODUCT COVERED:

*USR, CNR - Switches, Industrial Control, Model Series SMC, followed by -S or -SH, followed by -2, followed by 03 to 48, followed by D, followed by M, followed by 1, followed by -B, -F or blank, maybe followed by any special codes.

Model Series SMA, followed by -S or -SH, followed by -1, followed by 03 to 48, followed by D, followed by M, followed by 1, followed by -B, -F or blank, maybe followed by any special codes.

ELECTRICAL RATINGS: (SMC)

Model	A	V	Pole	Contacts	Load	O.L./End Cycles	Coil Volts	Hz
*SMC	5	240 ac	2	NO	RES	6000	3-48 dc	50/60
*	5	30 dc	2	NO	RES	6000	3-48 dc	
*	2	240 ac	2	NO	GP	6000	3-48 dc	

ELECTRICAL RATINGS: (SMA)

Model	A	V	Pole	Contacts	Load	O.L./End Cycles	Coil Volts	Hz
*SMA	10	250 ac	1	NO	RES	6000	3-48 dc (Coil Sensivity 250-540 mW)	50/60
*	10	30 dc	1	NO	RES	6000	3-48 dc (Coil Sensivity 250-540 mW)	
*	3	250 ac	1	NO	GP	6000	3-48 dc (Coil Sensivity 250-540 mW)	

GP - General Purpose (General Use)

RES - Resistive

NOMENCLATURE:

*SMC	-S	-2	12	D	M	1 -	F -	XX
I	II	III	IV	V	VI	VII	VIII	IX

- *I. Type
SMC (2 Pole Only)
- *II. Protective Construction
SH: Sealed type washable
S: Sealed type
- *III. Number of Poles
2 - 2 pole (SMC)
- *IV. Coil Voltage
Any voltage between 3 Vdc and 48 Vdc.
- V. Coil Sensitivity
D: 540 mW
L: 250 mW
- *VI. Contact Form
M: 2 Form A
- VII. Contact Material
1: AgCdO
- VIII. Insulation System
B : Class 130(B)
F : Class 155(F)
Blank: Standard Type
- IX. Special Code
Additional numbers or letters, which don't effect construction.

NOMENCLATURE:

SMA	-S	-1	12	D	M	1 -	F -	XX
I	II	III	IV	V	VI	VII	VIII	IX

- I. Type
SMA (1 Pole Only)
- II. Protective Construction
SH: Sealed type washable
S: Sealed type
- III. Number of Poles
1 - 1 pole
- IV. Coil Voltage
Any voltage between 3 Vdc and 48 Vdc.
- V. Coil Sensitivity
D: 540 mW
L: 250 mW
- VI. Contact Form
M: 1 Form A
- VII. Contact Material
1: AgCdO
- VIII. Insulation System
B : Class 130(B)
F : Class 155(F)
Blank: Standard Type
- IX. Special Code
Additional numbers or letters, which don't effect construction.