

File E179745
Project 97SC15092

April 17, 1998

REPORT

ON

COMPONENT - SWITCHES, INDUSTRIAL CONTROL

Dongguan Sanyou Electrical Appliances Co. Ltd.
Guangdong, China

Copyright © 1998 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

DESCRIPTION

PRODUCT COVERED:

*USR, CNR - Magnetic, Switches, Industrial Control, SRDH Series, followed by -S or -SH, followed by -1, followed by 03 to 48, followed by D, followed by M or B or blank, followed by 1, followed by blank or -B or -F, maybe followed by any special codes.

GENERAL:

The devices are enclosed type magnetically operated, single-pole double-throw relays, with normally open and normally closed contacts with single stable, one coil latching.

RATINGS:

Contact -

10 A, 240 V ac, Resistive, 6000 Cycles
10 A, 120 V ac, Resistive, 6000 Cycles
10 A, 28 V dc, Resistive, 6000 Cycles
3 A, 125 V ac General Use, 6000 Cycles

Coil -

3-48 V dc

NOMENCLATURE:

*

<u>SRDH</u>	<u>-S</u>	<u>-1</u>	<u>12</u>	<u>D</u>	<u>M</u>	<u>1</u>	<u>-F</u>	<u>-XX</u>
I	II	III	IV	V	VI	VII	VIII	IX

- I. Basic Designation: SRDH
- II. Protective Construction:
S - Sealed
SH - Sealed washable
- III. Number of Poles:
1 - 1 pole
- IV. Coil Voltage:
Any voltage between 3 Vdc and 48 Vdc
- V. Coil Sensitivity:
D - 0.36 W
- VI. Contact Form:
M - 1 Form A
B - 1 Form B
Blank - 1 Form C
- VII. Contact Material:
1 - AgCdO
- VIII. Insulation System:
Blank - Standard Type
B - Class 130(B)
F - Class 155(F)
- VIII. Special Code
Additional numbers or letters, which don't effect construction.